



Main

Product	Surge protection device
Range	Surgelogic

Complementary

Voltage Rating	600Y/347 V AC
MCOV	510 V
SCCR	200 kA
Surge Current	40 kA per phase
Nominal Discharge Current	10 kA
Number of Phases	3 phase
Wiring Configuration	4-wire
Local Signalling	Status LED green normal operation
Cable length	24 in (609.6 mm)
Height	3 in (76.2 mm)
Width	3.6 in (91.4 mm)
Depth	3.4 in (86.4 mm)

Environment

Ambient Operating	149 °F (65 °C)
Enclosure Rating	NEMA 4X
Enclosure Material	Black Plastic
Standards	UL 1449:ed. 4: type I NEC 285: type I CSA C22.2 No 8

Ordering and shipping details

Category	US1DE1B08462
Discount Schedule	DE1B
GTIN	785901210887
Returnability	Yes
Country of origin	US

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.100 in (7.874 cm)
Package 1 Width	3.900 in (9.906 cm)
Package 1 Length	5.0000000000 in (12.7 cm)
Package 1 Weight	12.480 oz (353.802 g)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------