VHU362

Safety switch, VisiPacT, heavy duty, unfused, viewing window, NEMA 1, 600V, 60A, 3 pole



Main

| IVIAILI | |
|---------------------------|--|
| Product | Single Throw Safety Switch |
| Duty Rating | Heavy duty |
| Device Application | Heavy application |
| Disconnect Type | Non-fusible disconnect |
| Factory Installed Neutral | Field installed kit available |
| Number of Poles | 3 |
| Current Rating | 60 A |
| Voltage Rating | 600 V AC/DC |
| Enclosure Rating | NEMA 1 steel |
| Motor power hp | 10 Hp at 240 V AC 50/60 Hz for 1 phase motors 20 Hp at 240 V AC 50/60 Hz for 3 phase motors 25 Hp at 480 V AC 50/60 Hz for 1 phase motors 50 Hp at 480 V AC 50/60 Hz for 3 phase motors 30 Hp at 600 V AC 50/60 Hz for 1 phase motors 60 Hp at 600 V AC 50/60 Hz for 3 phase motors 10 Hp at 250 V DC 30 hp at 600 V DC |

Complementary

| Mounting Type | Surface |
|-----------------------|--|
| Electrical Connection | Lugs |
| Wiring configuration | 3-wire |
| Wire Size | AWG 14AWG 3 copper AWG 12AWG 3 aluminium |
| Tightening torque | 50 Lbf.In (5.6 N.m) (AWG 3) 45 Lbf.In (5.08 N.m) (AWG 6AWG 4) 40 Lbf.In (4.5 N.m) 0.013 in² (8.367 mm²) (AWG 8) 50 lbf.in (5.6 N.m) 0.0030.008 in² (2.065.261 mm²) (AWG 14AWG 10) |
| Depth | 7.04 in (178.82 mm) |
| Width | 8.91 in (226.31 mm) |
| Height | 18.184 in (461.874 mm) |
| Net Weight | 15.4 lb(US) (7 kg) |
| Grounding Kit | Field installed kit available |
| Service Entrance | Suitable service entrance for USA Suitable service entrance for Mexico |

Environment

| Certifications | cULus Listed File E2875 |
|----------------|---|
| Standards | UL98 CSA C22.2 No 4 NOM-003-SCFI-2000 |

Ordering and shipping details

| Category | US10DE100008 |
|-------------------|---------------|
| Discount Schedule | 0DE1 |
| GTIN | 3606485894652 |
| Returnability | Yes |
| Country of origin | US |
| | |

Packing Units

| 0 | |
|------------------------------|------------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.300 in (18.542 cm) |
| Package 1 Width | 10.700 in (27.178 cm) |
| Package 1 Length | 19.800 in (50.292 cm) |
| Package 1 Weight | 14.749 lb(US) (6.690 kg) |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 40 |
| Package 2 Height | 40.000000000 in (101.600 cm) |
| Package 2 Width | 40.000000000 in (101.600 cm) |
| Package 2 Length | 48.000000000 in (121.920 cm) |
| Package 2 Weight | 620.000 lb(US) (281.227 kg) |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|---|
| California proposition 65 | "WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov" |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant CEU RoHS Declaration |
| Sustainable packaging | Yes |
| RoHS exemption information | ₽ Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |