

PRODUCT SHEET

Light duty bar hangers

Improved design for stronger
and faster installation

Steel City[®]



Steel City® light duty bar hangers

The perfect partner to your Steel City® fixture box

Installing a fixture box between studs has never been easier. Our new design simplifies the work of electricians and contractors.

Features

- Pre-set for 1½ in. deep fixture box and ½ drywall
- For use with ¾ in., ½ in. and ⅝ in. drywall and plaster
- End plate locator tab is scored and marked for lath and plaster drywall applications with standard and deep boxes



O1 Series with stud



O2 Series with fastener



Note: This product is available with either a stud or a fastener.



Catalog number	Description	Maximum load capacity	Length
6010-DW-25	Adjustable bar hanger with score marks for ¾ in., ½ in., and ⅝ in. drywall and plaster depths. Packaged complete with stud. Maximum load capacity is 50 lbs.	50 lb.	10½ in. to 18 in.
6010-ADW-25	Adjustable bar hanger with score marks for ¾ in., ½ in., and ⅝ in. drywall and plaster depths. Packaged complete with stud. Maximum load capacity is 50 lbs.	50 lb.	1½ in. to 25 in.
6011-DW-25	Adjustable bar hanger with score marks for ¾ in., ½ in., and ⅝ in. drywall and plaster depths. Packaged complete with stud. Maximum load capacity is 50 lbs.	50 lb.	10½ in. to 18 in.
6011-ADW-25	Adjustable bar hanger with score marks for ¾ in., ½ in., and ⅝ in. drywall and plaster depths. Packaged complete with stud. Maximum load capacity is 50 lbs.	50 lb.	14½ in. to 25 in.
54151 NF	Bar hanger with 4 in. diameter x 1½ in. deep octagonal box, ½ in. knockouts, drawn construction, with non-metallic cable clamps for use with non-metallic sheathed cable.	50 lb.	10½ in. to 18 in.
54151 NO	Bar hanger with 4 in. diameter x 1½ in. deep octagonal box, ½ in. knockouts, drawn construction, with non-metallic cable clamps for use with non-metallic sheathed cable.	50 lb.	14½ in. to 25 in.
54151 NG	Bar hanger with 4 in. diameter x 1½ in. deep octagonal box, ½ in. knockouts, drawn construction, with non-metallic cable clamps for use with non-metallic sheathed cable.	50 lb.	10½ in. to 18 in.
54151 NP	Bar hanger with 4 in. diameter x 1½ in. deep octagonal box, ½ in. knockouts, drawn construction, with non-metallic cable clamps for use with non-metallic sheathed cable.	50 lb.	14½ in. to 25 in.
54151 AF	Bar hanger with 4 in. diameter x 1½ in. deep octagonal box, ½ in. knockouts, drawn construction, with armored cable clamps for use armored/metal clad cable.	50 lb.	10½ in. to 18 in.
54151 J1/2	Bar hanger with 4 in. diameter x 1½ in. deep octagonal box, ¾ in. knockouts, drawn construction, for use with conduit. Offset for ½ in., ¾ in., or ⅞ in. plaster.	50 lb.	10½ in. to 18 in.

Please ask your Thomas & Betts sales representative for a complete catalog of quality Thomas & Betts electrical products or visit us at www.tnb.com. For customer service, call 1-800-816-7809. For technical questions, call 1-888-862-3289.

© 2018 Thomas & Betts Corporation. All rights reserved. Printed in the U.S.A.
4/18 GM7839

Thomas & Betts Corporation
Electrification Products Division of ABB
8155 T&B Boulevard
Memphis, TN 38125
901-252-5000
www.tnb.com

Thomas & Betts
A Member of the ABB Group