

TPI Industrial Assembled Circulator Heads and Mounts

Features

- Steel construction with silver/gray powder coated; steel motor housing painted black
- Direct drive, Totally Enclosed Air-Over (TEAO) motor generating up to 12,000-CFM's
- Aluminum 3-paddle blade system with steel hub and cast aluminum spider connections
- All models contain a pull-chain switch and 12' long SJT-Type cord with grounded plug
- All models, except HDH-36, contain self-locking retaining clips to secure front/rear grills and meet OSHA safety requirements
- HDH-36 model operates at single speed, contains interlocking front/rear grills and includes a heavy-duty wall mounting bracket inside the carton
- HDH-GJR Series contains a 12' long SJT-Type cord with grounded plug and 18" long drop down cord assembled with an electrical (off, on low/high) switch enclosure
- Fully-Assembled ready for plug-&-play operation offered in Non-Oscillating (Stationary) and Oscillating fan heads in 20", 24" or 30" diameter sizes; mounts sold separately
- Oscillating models rotates in a 90° arc or can be locked in a fixed position
- Metal gears in the oscillating model allow the fan to operate at a maximum 30° downward tilt
- Motor warranty ranges from 1, 3 and 5-years
- Made in the U.S.A. with domestic and foreign components

Motor Specifications

- 2-Speed
- 1 Phase, 120V
- Ball bearing
- Frame size: 48
- Totally enclosed
- Permanent split capacitor
- Permanently lubricated
- 1/2" Shaft

DIMENSIONS	
20"	22" Diameter x 14.5" Depth
24"	27" Diameter x 14.5" Depth
30"	33.5" Diameter x 14.5" Depth



WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.



ACM-IHP-HDH Series



HDH-G-JR Series
Drop-Down Plug
and Hinged Guard



ACH-O Series
Oscillating Motor

Standard Models

H.P.	BLADE SIZE	MFG MODEL NUM- BER	MFG CATALOG NUMBER	FAN HEAD TYPE	CFM*	VELOCITY PROFILE	RPM	AMPS	WT. (LBS)
						CFM / Area Sq Ft			
1 Year Warranty									
Industrial 1/4	20"	ACH 20	08684702	STATIONARY	3000 / 2600	5000 / 200	1100 / 900	2.4	39
	24"	ACH 24	07961602		3800 / 3400	6000 / 240	1100 / 800	2.5	40
	30"	ACH 30	07961702		4300 / 3800	7200 / 250	1100 / 800	2.7	44
3 Year Warranty									
High Performance 1/3	24"	IHP 24-H	07989802	STATIONARY	4300 / 3900	6000 / 240	1100 / 800	2.8	40
	30"	IHP 30-H	07989902		5400 / 4700	7200 / 250	1100 / 800	3	44
	36"	HDH 36	08197802		6970	12000 / 325	1100	5.2	90
5 Year Warranty									
Heavy Duty 1/2	24"	HDH 24-G	08539202	STATIONARY	5600 / 4900	7500 / 260	1100 / 800	3.5	44
	30"	HDH 30-G	08528602		6800 / 6000	8000 / 270	1100 / 800	4	48
	24"	HDH 24-GJR	08539202		5600 / 4900	7500 / 260	1100 / 800	3.5	44
	30"	HDH 30-GJR	08528602		6800 / 6000	8000 / 270	1100 / 800	4	48
1 Year Warranty									
Industrial Oscillating 1/4	20"	ACH 20-O	08684802	OSCILLATING	3000 / 2600	5000 / 200	1100 / 900	2.4	43
	24"	ACH 24-O	07963602		3800 / 3400	6000 / 240	1100 / 800	2.5	44
	30"	ACH 30-O	07963702		4300 / 3800	7200 / 250	1100 / 800	2.7	48

*Measured 2 feet from face of fan

HDH-36 Note: Wall mount only, mount included, unit imported to TPI specifications.

TPI offers six factory assembled and tested fan mounts that can be used with any of the non-oscillating TPI Industrial heads.