



V Series

FD9389-EHTV-V2

5MP Outdoor Fixed Dome AI Camera



Technical Specifications

| System Information | |
|--------------------|---------------------------------|
| CPU | Multimedia SoC (System-on-Chip) |
| Flash | 8 GB |
| RAM | 1 GB |

| Camera Specifications | |
|-------------------------|---|
| Image Sensor | 1/2.7" Progressive CMOS |
| Max. Resolution | 2560x1920 (5MP) |
| Lens Type | Motorized, Vari-focal, Remote Focus |
| Focal Length | f = 2.8~10 mm |
| Aperture | F1.8(W) ~ F2.74(T) |
| Iris Type | Fixed iris |
| Field of View | 95°~41° (Horizontal) 69°~31° (Vertical) 127°~51° (Diagonal) |
| Shutter Time | 1/5 sec. to 1/32,000 sec. |
| WDR Technology | WDR Pro |
| Day/Night | Yes |
| Removable IR-cut filter | Yes |
| Illuminators | Built-in IR illuminators, effective up to 30 meters with Smart IR, IR LED * 4 |
| Minimum Illumination | 0.06 lux @ F1.8 (Color) 0.01 lux @ F1.8 (B/W) 0 lux with IR illumination on |
| Pan Range | >350° |

| | |
|-------------------------------|---|
| Tilt Range | 80° |
| Rotation Range | ±175° |
| Pan/Tilt/Zoom Functionalities | ePTZ: 48x digital zoom (4x on IE plug-in, 12x built-in) |
| Storage | Seamless Recording to MicroSD/SDHC/SDXC card (1TB capacity supported) and recording to network-attached storage (NAS) |
| Built-in Installation Aids | Remote focus, remote zoom |

Video

| | |
|--------------------|---|
| Compression | H.265, H.264, MJPEG |
| Maximum Frame Rate | 30 fps @ 2560x1920 (5MP) (WDR on) 30 fps @ 2560 x1440 (4MP) (WDR on) 60 fps @ 1920x1080 (2MP) (WDR off) encode mode: mode 0 for all |
| Maximum Streams | 3 video streams (Up to 8 configurable profiles) |
| S/N Ratio | > 55dB |
| Dynamic Range | 120 dB |
| Video Streaming | Adjustable resolution, quality and constant bit rate control, Smart Stream III |
| Image Settings | <p>General settings video title and time stamp overlay, video orientation (flip, mirror, rotation), day/night settings</p> <p>Illuminators illuminators, anti-overexposure</p> <p>Image settings white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR, EIS (built-in gyro sensor), scene mode (auto, deblur)</p> <p>Exposure BLC, HLC, exposure control(exposure level, iris adjustment, exposure time, gain control, iris mode), AE speed adjustment, WDR</p> <p>Focus zoom, focus</p> <p>Privacy mask Scheduled profile settings</p> |

Audio

| | |
|------------------|-----------------------------|
| Audio Capability | One-way Audio |
| Compression | G.711, G.726, MPEG-2 AAC-LC |
| Interface | Built-in microphone |
| Effective Range | 5 meters |

Network

| | |
|-----------|---|
| Users | Live viewing for up to 10 clients |
| Security | Access list, Account block , Audit log, Configurable password strength protection, CSRF protection, Digest authentication, HTTPS , IEEE 802.1x, Secure boot, Session timeout, Signed firmware, Trend Micro IoT Security (Brute force attack event, Cyberattack event, Quarantine event), User access log, User account management |
| Protocols | 802.1X, ARP, Bonjour, CIFS/SMB, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTP, PPPoE, QoS (CoS/DSCP), RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS 1.2, UDP, UPnP |

| | |
|-----------|---|
| Interface | 10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard. |
| ONVIF | Profile G, S, T supported, specification available at www.onvif.org |

AI Analytics

| | |
|------------------------------------|---|
| Compute Capability | SoC with built-in hardware deep learning accelerator |
| Vision Object Analytics | Object Detection people, vehicle (4-wheeled) Path Extraction |
| Application | Deep Learning VCA (Smart Motion Detection, Smart VCA) Smart Motion Detection (Five-window video motion detection, People detection, Vehicle detection, Time filter), Smart VCA (Intrusion detection, Loitering detection, Line crossing detection, Unattended object detection, Missing object detection, Face detection, Crowd detection) |
| Application available with license | Running detection, Parking Violation Detection, Restricted Zone Detection Support for more analytic applications and free trial, please visit vivotek.com/video-analytics |
| AI-powered Image Enhancement | Smart IR III |

Solution Integration

| | |
|------------------------|---|
| VADP Package | Trend Micro IoT Security (3-year free trial) |
| Video Motion Detection | Motion Detection (Five-window video motion detection) |

Alarm and Event

| | |
|---------------|--|
| Event Trigger | Audio detection, camera tampering detection, cybersecurity events (brute force attack event, cyberattack event, quarantine event), manual trigger, motion detection, periodical trigger, recording notification, SD card life expectancy, shock detection, system boot |
| Event Action | Event notification via camera link, email, HTTP, FTP/SFTP, NAS server, SD card File upload via email, HTTP, FTP/SFTP, NAS server, SD card |

General

| | |
|-------------------|--|
| Connectors | RJ-45 cable connector for Network 10/100 Mbps PoE connection |
| LED Indicator | System power and status indicator |
| Power Input | IEEE 802.3af PoE Class 0 |
| Power Consumption | Max: 12.3W (IR on) Max: 9.9W (IR off) |
| Dimensions | ø 129 x 94 mm |
| Weight | 610 g |
| Certifications | EMC CE (EN55032, EN55024 Class A, EN50121-4), FCC (FCC Part 15 Subpart B Class A), RCM (AS/NZS CISPR32 Class A), VCCI (VCCI-CISPR 32 Class A) Safety UL (UL62368-1), CB (IEC/EN 62368-1, IEC/EN 60950-22, IEC/EN 62471) Environment IK10 (IEC 62262), IP66 (IEC 60529) IA BIS (IS 13252), BSMI (EMC: CNS 13438, Safety: CNS 14336-1) |

| | |
|-----------------------|---|
| Operating Temperature | Starting Temperature: -30°C ~ 50°C (-13°F ~ 122°F) Working Temperature(IR on): -40°C ~ 60°C (-40°F ~ 140°F) (IR off) -40°C ~ 50°C (-40°F ~ 122°F) (IR on) |
| Humidity | 98% RH (non-condensing) |

System Requirements

| | |
|------------------|---|
| Operating System | Microsoft Windows 10/8/7 Mac 10.12 (Chrome only) |
| Web Browser | Chrome 58.0 or above Internet Explorer 11 |
| Other Players | VLC: 1.1.11 or above |

Included Accessories

| | |
|------------------|---|
| Packing Contents | Quick installation guide, alignment sticker, screw pack |
|------------------|---|

DORI (EN 62676-4 Standard)

| | |
|--------------------------------|---|
| Detection (25PPM/ 8PPF) | Wide: 65.8 m (216.0 ft) Tele: 140.5 m (461.0 ft) |
| Observation (63PPM/ 19PPF) | Wide: 26.1 m (85.7 ft) Tele: 55.8m (182.9 ft) |
| Recognition (125PPM/ 38PPF) | Wide: 13.2 m (43.2 ft) Tele: 28.1m (92.2 ft) |
| Identification (250PPM/ 76PPF) | Wide: 6.6 m (21.6 ft) Tele: 14.0m (46.1 ft) |