



Winnie Industries

MANUFACTURER OF FASTENING SUPPORTS

Magnetic

Ultra Heavy-Duty Mounting Magnet with Bridle Ring

**Extremely strong, fast, and cost-effective cable management solution
for mounting on THIN metal**



Features:

- Permanent nine-pole charged rare earth neodymium magnet
- Exceptionally strong when compared to conventional neodymium pot magnets
- Vertical pull force up to 150 lb on sheet metal
- Due to the intense magnetic attraction at the surface, will not easily slide like other magnets
- Magnet's black epoxy coating provides corrosion resistance
- Crafted from heavy-duty, zinc plated steel which allows for great durability & corrosion resistance
- Available in 1.25" and 2" ring diameter with 1.5" or short stem
- Designed with open loop for quick & easy cable installation
- Provides support for CAT5e/CAT6 category cable, low-voltage wire, coax, signal & control cable and electrical wire up to 600V
- Quick & easy installation without specialized tools and equipment
- Sticks through oil, grease and dirty areas
- Long-lasting performance in a variety of demanding conditions



Application:

- Provides support in the distribution of wire & cable bundles
 - Network/Data
 - Telcom/Voice
 - Broadband, Satellite, CCTV
 - Low Voltage/Security/Fire Alarm
 - Signal/Control Cable
 - Electrical Wire

Installation:

- Secures to steel beams, ceiling decks, sheet metal, metal joists, van walls & other ferromagnetic surfaces
- **Engineered for max attachment to thin metal**

engineered and manufactured to make installs easier

winnieindustries.com



5420 Newport Dr. Unit 62
Rolling Meadows, IL 60008

224-993-0011
sales@winnieindustries.com



Magnetic

Part Numbers

Part #	Description	Box Qty	12-digit UPC
WUMAG-WBR4T125	1.25" Bridle Ring, 1.5" Stem, 150 lb Magnet, UHD	10	811443033698
WUMAG-WBR4T200	2" Bridle Ring, 1.5" Stem, 150 lb Magnet, UHD	10	811443033681
WUMAG-WBR125SHORT	1.25" Bridle Ring, Short Stem, 150 lb Magnet, UHD	10	811443033711
WUMAG-WBR200SHORT	2" Bridle Ring, Short Stem, 150 lb Magnet, UHD	10	811443033704



- | Reduces job labor costs on permanent or temporary installations |
- | Very versatile and are designed with an open loop for easy cable insertion |
- | Engineered to hold to ferromagnetic surfaces thinner than 1mm |
- | Magnet epoxy coating provides outstanding chemical resistance, durability, and toughness |
- | Fast and cost-effective solution to support voice, security, and video cable |
- | If using a bridler ring with high performance data cable a saddle is required to ensure proper bend |
- | Non-continuous supports may not exceed spacing of 5' per TIA 569-C.9.7 |

Related Items

Part #	Description
075GRIPTAPE	3/4" Grip Tape, 75ft, Black
WUMAG-1420UHD	150 Lb Ultra Heavy-Duty Mounting Magnet, UHD
WUMAG-WBR4T200SDL	2" Bridle Ring, 1.5" Stem, 150 lb Magnet, Saddle, UHD
WBRS200	2" Saddle Only for Bridler Ring



WUMAG-WBR4T200SDL
Use with high performance category cable

Nothing else on the Market Compares

Magnet Specifications:

- Size: 2" x 3/8" (50.8mm x 9.5mm)
- Threaded Hole: 1/4 x 20
- Vertical Pull Force: 150 lb
- Coating: Epoxy
- Material: Magnet: Neodymium (NdFeB)
Fender Washer: Steel
- Temperature Tolerance: -40°F - 176°F (-40°C - 80°C)

Specify Winnie...

- ✓ Since 2015
- ✓ Family-Owned & Operated
- ✓ Personal & Friendly Customer Service

- + Please handle neodymium magnets with care
- + Keep neodymium magnets away from anyone with a pacemaker
- + Magnets are not toys and should be kept away from children and pets
- + Large powerful magnets can pinch your fingers or cause other injuries, use caution

